



Welcome United States Patent and Trademark Office

Search Results[BROWSE](#)[SEARCH](#)[IEEE XPLORE GUIDE](#)[SUPPORT](#)

Results for "((network traffic irregular time interval<in>metadata) <and> (receiver node<in>..."

Your search matched 0 documents.

A maximum of 100 results are displayed, 25 to a page, sorted by **Relevance** in **Descending** order. [e-mail](#) [printer friendly](#)» [Search Options](#)[View Session History](#)[New Search](#)**Modify Search**

((network traffic irregular time interval<in>metadata) <and> (receiver node<in>met

Search ☐ Check to search only within this results setDisplay Format: ☒ Citation ☐ Citation & Abstract» **Key**

IEEE JNL	IEEE Journal or Magazine
IEE JNL	IEE Journal or Magazine
IEEE CNF	IEEE Conference Proceeding
IEE CNF	IEE Conference Proceeding
IEEE STD	IEEE Standard

No results were found.

Please edit your search criteria and try again. Refer to the Help pages if you need assistance revising your search.

Indexed by
 Inspec®[Help](#) [Contact Us](#) [Privacy & Security](#) [IEEE.org](#)

© Copyright 2006 IEEE – All Rights Reserved



Welcome United States Patent and Trademark Office

Search Results[BROWSE](#)[SEARCH](#)[IEEE XPLORE GUIDE](#)[SUPPORT](#)

Results for "((time interval <in>metadata) <and> (node<in>metadata))<and> (network..."

Your search matched **0** documents.A maximum of **100** results are displayed, **25** to a page, sorted by **Relevance** in **Descending** order. [e-mail](#) [printer friendly](#)**» Search Options**[View Session History](#)[New Search](#)**Modify Search****Search** ☐ Check to search only within this results setDisplay Format: ☒ Citation ☐ Citation & Abstract**» Key**

IEEE JNL IEEE Journal or Magazine

IEE JNL IEE Journal or Magazine

IEEE CNF IEEE Conference Proceeding

IEE CNF IEE Conference Proceeding

IEEE STD IEEE Standard

No results were found.

Please edit your search criteria and try again. Refer to the Help pages if you need assistance revising your search.

Indexed by
 Inspect®[Help](#) [Contact Us](#) [Privacy & Security](#) [IEEE.org](#)

© Copyright 2006 IEEE – All Rights Reserved



USPTO

[Subscribe \(Full Service\)](#) [Register \(Limited Service, Free\)](#) [Login](#)

 Search: ☒ The ACM Digital Library ☐ The Guide

irregular and time and interval and network and traffic and rec

THE ACM DIGITAL LIBRARY


[Feedback](#) [Report a problem](#) [Satisfaction survey](#)

Terms used

irregular and time and interval and network and traffic and receiver and sender and node

 Found 49,619 of
192,172

 Sort results
by


[Save results to a Binder](#)
[Try an Advanced Search](#)
[Try this search in The ACM Guide](#)

 Display
results


[Search Tips](#)

[Open results in a new window](#)

Results 1 - 20 of 200

 Result page: [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [next](#)

Best 200 shown

 Relevance scale ☐ ☐ ☐ ☐ ☐

1 [Measurement-based models of delivery and interference in static wireless networks](#)



Charles Reis, Ratul Mahajan, Maya Rodrig, David Wetherall, John Zahorjan

 August 2006 **ACM SIGCOMM Computer Communication Review , Proceedings of the 2006 conference on Applications, technologies, architectures, and protocols for computer communications SIGCOMM '06**, Volume 36 Issue 4

Publisher: ACM Press

 Full text available: pdf(407.85 KB) Additional Information: [full citation](#), [abstract](#), [references](#), [index terms](#)

We present practical models for the physical layer behaviors of packet reception and carrier sense with interference in static wireless networks. These models use measurements of a real network rather than abstract RF propagation models as the basis for accuracy in complex environments. Seeding our models requires N trials in an N node network, in which each sender transmits in turn and receivers measure RSSI values and packet counts, both of which are easily obtainable. The models then predict ...

Keywords: RSSI, interference, modeling

2 [Achieving bounded fairness for multicast and TCP traffic in the Internet](#)



Huayan Amy Wang, Mischa Schwartz

 October 1998 **ACM SIGCOMM Computer Communication Review , Proceedings of the ACM SIGCOMM '98 conference on Applications, technologies, architectures, and protocols for computer communication SIGCOMM '98**, Volume 28 Issue 4

Publisher: ACM Press

 Full text available: pdf(1.85 MB) Additional Information: [full citation](#), [abstract](#), [references](#), [citations](#), [index terms](#)

There is an urgent need for effective multicast congestion control algorithms which enable reasonably fair share of network resources between multicast and unicast TCP traffic under the current Internet infrastructure. In this paper, we propose a quantitative definition of a type of bounded fairness between multicast and unicast best-effort traffic, termed "essentially fair". We also propose a window-based Random Listening Algorithm (RLA) for multicast congestion control. The algorithm is proven ...

Keywords: Internet, RED and drop-tail gateways, flow and congestion control, multicast, phase effect

3

[MANETs: Gateway adaptive pacing for TCP across multihop wireless networks and the Internet](#)



[Google](#)[Web](#) [Images](#) [Video](#) [News](#) [Maps](#) [more »](#)

irregular time interval network traffic receiver n

[Advanced Search](#)
[Preferences](#)**Web** Results 1 - 10 of about 23,200 for **irregular time interval network traffic receiver node sender node**. (0.29 seconds)**EP1122917 Microsoft european software patent - System and method ...**

The method also includes generating a plurality of **irregular interval** ... A computer **network** comprising: a **receiver node**; and at least one **sender node** ...
 gauss.ffii.org/PatentView/EP1122917 - 66k - [Cached](#) - [Similar pages](#)

Nat' Academies Press, Traffic Management for High-Speed Networks ...

At various **times**, the **receiver** sends credits to the **sender** indicating ... Adaptive buffer allocation can be implemented at the **sender** or **receiver node**. ...
 newton.nap.edu/books/0309057981/html/6.html - 52k - [Cached](#) - [Similar pages](#)

[PDF] A Statistical Method of Packet Loss Type Discrimination in Wired ...

File Format: PDF/Adobe Acrobat

intermediate **node**. The resultant inter-arrival **time** ... **[Sender]**. RTP. CBR. UDP. CBR. **[Receiver]**. RTP. N3. N2. Back **Traffic**. Source **Traffic** ...

ieeexplore.ieee.org/iel5/10599/33505/01593066.pdf?isnumber=33505&arnumber=1593066
 - [Similar pages](#)

[PDF] Load Balancing In Distributed Shared Memory Systems - Performance ...

File Format: PDF/Adobe Acrobat

tentially omitted if the **receiver** and **sender** are sharing. same portion of data at the first place. ... spect to each **node**. To avoid heavy **network traffic** ...

ieeexplore.ieee.org/iel3/4442/12602/00581502.pdf?arnumber=581502 - [Similar pages](#)

[[More results from ieeexplore.ieee.org](#)]

SAE Technical Paper Template

Each **node** in this real-time **network** refers to this global **time** and the point ... If the successor of the **sender node** hasn't received the expected message on ...

www.vmars.tuwien.ac.at/projects/xbywire/projects/new-bosch.htm - 52k -

[Cached](#) - [Similar pages](#)

Architectural Support for Efficient Multicasting in Irregular Networks

Such a computing environment typically consists of processing **nodes** interconnected through a switch-based **irregular network**. Many of the problems that were ...

doi.ieeecomputersociety.org/10.1109/71.926170 - [Similar pages](#)

\bf The Use of End-to-end Multicast Measurements for ...

Starting with the set of **receiver nodes** R, select the pair of **nodes** j,k in ... and queue overflow at **network nodes** as multicast probes compete with **traffic** ...

gaia.cs.umass.edu/minc/minc-comm/index.html - 44k - [Cached](#) - [Similar pages](#)

[PS] Credit-Based Flow Control for ATM NetworksFile Format: Adobe PostScript - [View as Text](#)

Section 3 presents two general kinds of **network traffic** that. flow control must cope with. ... **sender** or **receiver node**. As depicted by Figure 3, in a ...

pdos.csail.mit.edu/~rtm/papers/ieee-network395.ps - [Similar pages](#)

[PDF] Topology Discovery Schema for All Optical Packet-Switched NetworksFile Format: PDF/Adobe Acrobat - [View as HTML](#)

place in the **network node** closest to the **receiver**. ... The routing decision for a packet has to be made during the **time interval** between receiving ...

www.comp.brad.ac.uk/het-net/HET-NETs04/CameraPapers/P79.pdf - [Similar pages](#)

[PS] Investigating the Synchronous Bandwidth Allocation in an FDDI ...File Format: Adobe PostScript - [View as Text](#)

including both the **sender** and **receiver** hosts, and the **network**, and allowing multiple applications,. communicating with applications on other **nodes** through ...
research.cs.tamu.edu/realtime/publication/feng-tech-95.ps.gz - [Similar pages](#)

Result Page: [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) **Next**

Try [Google Desktop](#): search your computer as easily as you search the web.

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2006 Google